

## **Technical Specification**

Luckinslive 389086428

Product Code: CL036

Description: 13A 2 Gang Double Pole Switched Socket Outlet





## **General Information**

Dimensions (mm)	140 (W) × 80 (H) × 42 (D)				
Plate Fixing Centres - Horizontal (mm)	120.6				
Style	Metal Clad				
Colour	Grey				
Insert Colour	White				
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel		Insert & Rocker Switch: Urea		
	Rear Housing: Urea		Terminals: Brass		
	Terminal Screws: Steel & Yellow Passivated		Contacts: Silver "on-lay" Copper / Brass		
	Internal Busbars: Formed Pressed Bra	ISS	Earth Strap: Mild Stee	el	
Operating Voltage (AC)	250		Frequency (Hz)	50	
Resistive Load Rating (A)	13				
Termination Type	Screw				
Terminal Size (mm)	Ø5 Terminal Torque Value (Nm) 2			2	
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4				
Double Pole Switch	Yes				
Twin Earth Terminals	Yes				
Supplied Back Box Depth (mm)	40				
Back Box Knockouts - Total (mm)	7 x Ø20				
Back Box Knockouts - Top (mm)	3 x Ø20 Back B	Back Box Knockouts - Sides (mm)		1 X Ø20	
Back Box Knockouts - Bottom (mm)	2 x Ø20 Back	Box Kno	ckouts - Rear (mm)	None	
Back Box Earth Terminal Supplied	Yes				
Ingress Protection	IP20				
Operational Temperature (°C)	-5 to +40				
Warranty (Years)	20				
Standards BS 1363-2					
Additional Information					

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









