

## SPECIFICATION SHEET

**Product Code**

CPC770++

**Product Description**

13A 2 Gang Switched UK Socket With USB Outlet


**General Information**

Dimensions	146mm x 86mm x 26.5mm
Finishes Available	CPC770: White, CPC770SV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	13A
Fixing Centres	120.6mm
Terminal Screw Size	4mm $\emptyset$
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup> , 1 x 6mm <sup>2</sup>
Switched	Yes
Double Pole	No
Twin Earth	Yes
USB Charging Outlet	5V DC, 2.1A
USB Output Connector	USB Type "A"
USB Standby Current	2mA
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

**Standards**

 BS 1363-2: 2016  
 BS EN 62368-1: 2014  
 BS EN 62680-1-1

## SPECIFICATION SHEET

**Product Code**

GPC770++

**Product Description**

13A 2 Gang Switched UK Socket With USB Outlet

**Additional Information**

Ensure that the mains supply is isolated before commencing installation.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.