

SPECIFICATION SHEET

Product Code

CPC771++

Product Description

13A 1 Gang Switched UK Socket With USB Outlet


General Information

Dimensions	86mm x 86mm x 38.5mm
Finishes Available	CPC771: White, CPC771SV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	13A
Fixing Centres	60.3mm
Terminal Screw Size	4mm \emptyset
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm ² , 2 x 4mm ² , 1 x 6mm ²
Switched	Yes
Double Pole	No
Twin Earth	Yes
USB Charging Outlet	5V DC, 2.1A
USB Output Connector	USB Type "A"
USB Standby Current	2mA
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

Standards

 BS 1363-2: 2016
 BS EN 62368-1: 2014
 BS EN 62680-1-1

SPECIFICATION SHEET

Product Code

GPC771++

Product Description

13A 1 Gang Switched UK Socket With USB Outlet

Additional Information

Ensure that the mains supply is isolated before commencing installation.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.