

## SPECIFICATION SHEET

**Product Code**

CPC803++

**Product Description**

10AX SP 3 Gang 1 Way Plate Switch


**General Information**

Dimensions	86mm x 86mm x 31.5mm
Finishes Available	CPC803: White, CPC803SV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	10AX (Suitable For Inductive Loads)
Fixing Centres	60.3mm
Terminal Screw Size	3mm $\emptyset$
Terminal Torque	0.8Nm
Terminal Capacity	2 x 4mm <sup>2</sup> Max.
Switched	Yes
Double Pole	No
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

**Standards**

BS EN 60669- 1: 1999 + A1: 2002 + A2: 2008

**Additional Information**

Ensure that the mains supply is isolated before commencing installation. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.