

## SPECIFICATION SHEET

### Product Code

CPC9835N++

### Product Description

1 Gang 13A Universal Switched Socket With Neon



### General Information

Dimensions	86mm x 86mm x 27.5mm
Finishes Available	CPC9835N: White, CPC9835NSV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate & Neon Lens: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	13A
Fixing Centres	60.3mm
Terminal Screw Size	4mm $\emptyset$
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup> , 1 x 6mm <sup>2</sup>
Switched	Yes
Double Pole	No
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

### Additional Information

Ensure that the mains supply is isolated before commencing installation. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

### Plug Compatibility

13A British Standard, 5A Round Pin, 2A Round Pin  
16A European Schuko, 2.5A European 2 Pin Flat,  
US 3 Pin, 10A Australian 3 Pin, 10A Chinese 3 Pin