

SPECIFICATION SHEET

Product Code

CPC9836N++

Product Description

2 Gang 13A Universal Switched Socket With Neon


General Information

Dimensions	146mm x 86mm x 25.5mm
Finishes Available	CPC9836N: White, CPC9836NSV: Silver (RAL 9006 (White Aluminium))
Material Composition	Front Plate & Neon Lens: Polycarbonate Insert, Switch & Base: Polycarbonate Terminals: Brass Plated Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass Silver "On-lay" Copper/Brass Contacts
Maximum Voltage	250V~ 50Hz
Current Rating	13A
Fixing Centres	120.6mm
Terminal Screw Size	4mmø
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm ² , 2 x 4mm ² , 1 x 6mm ²
Switched	Yes
Double Pole	No
Back Box Depth	35mm Minimum
Temperature Rating	-5° to +40°C
Warranty	10 Years (Domestic)

Additional Information

Ensure that the mains supply is isolated before commencing installation. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Plug Compatibility

13A British Standard, 5A Round Pin, 2A Round Pin
 16A European Schuko, 2.5A European 2 Pin Flat,
 US 3 Pin, 10A Australian 3 Pin, 10A Chinese 3 Pin