

Technical Specification

Product Code: CPCo36N

Description: 13A 2 Gang Double Pole Switched UK Socket With Neon



General Information

Dimensions (mm) 146mm (W) x 86mm (H) x 27.5mm (D)

Plate Dimensions (mm) 146mm (W) x 86mm (H) x 6.5mm (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Screwless Colour White

Insert Colour White

Materials Cover Plate & Neon Lens: Polycarbonate

Terminals: Brass Plated Steel

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Frequency (Hz) 50

Indicator Colour Red

Terminal Torque Value (Nm) 1.2

Insert, Switch & Base: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Operating Voltage (AC) 250

Resistive Load Rating (A) 13

Termination Type Screw

Terminal Size (mm) Ø4

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Number Of Socket Outlets 2 Double Pole Switch Yes

> Neon Indicator Yes

Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.











Specification is subject to change without notice. Errors & Omissions excluded.